Simple, One-hand Operation Couplings

Nordson MEDICAL's LinkTech line of 40AC quick connect couplings are produced in a durable natural acetal (POM) thermoplastic. These couplings are resistant to most mild chemicals and are manufactured to be trouble free for many years of service. They are available with internal shut-off valves or straight through designs. They are intuitive to use and make an audible "click" when coupled. The 40AC Series couplings interconnect with all other 40PP and 40CB Series couplings as well as other similar industry thumb-latch type couplings.



Features & Benefits

- Legacy metal thumb-latch couplings available with hose barb, PTF, push-in and threaded terminations
- Resistant to most mild chemicals
- Intuitive, easy-to-use design
- Audible click when coupled
- Available with internal shut-off valves or straight-through designs
- Interconnect with each other and with similar industry thumb-latch couplings

Specifications

Materials:

Bodies & Terminations: Acetal (POM) Internal Valves: Acetal (POM) Internal Valve Springs: 316 Stainless Steel O-rings: Buna-N (others available) Thumb-latch: Stainless Steel External Springs & Pins: Stainless Steel

Performance Ratings:

Operating Pressure: Vacuum to 120psi; (8.3bar) Temperature: -40°F to 180°F; (-40°C to 82°C) Flow Capacity: 1/4" (6.4 mm)

Fits Tubing IDs: 1/4" (6.4 mm) - 3/8" (9.5 mm)







1/4" Flow Size - Legacy Metal Latch

Part Style

Part Image

Open Flow Straight

1/4" (6.4 mm) tube ID & threaded 5/16" (7.9 mm) tube ID 3/8" (9.5 mm) tube ID & threaded Female and Male









Open Flow Panel Mount

1/4" (6.4 mm) tube ID 5/16" (7.9 mm) tube ID 3/8" (9.5 mm) tube ID Female and Male





Open Flow Elbow

1/4" (6.4 mm) tube ID 3/8" (9.5 mm) tube ID Male ONLY





Valved Straight

1/4" (6.4 mm) tube ID & threaded 5/16" (7.9 mm) tube ID 3/8" (9.5 mm) tube ID & threaded Female and Male





Valved Panel Mount

1/4" (6.4 mm) tube ID 5/16" (7.9 mm) tube ID 3/8" (9.5 mm) tube ID Female and Male





Valved Elbow

1/4" (6.4 mm) tube ID 3/8" (9.5 mm) tube ID Male ONLY



MAR-40AC-DS-01







Food Grade Durable Thumb-Latch Couplings

Nordson MEDICAL's LinkTech line of 40CB quick connect couplings are produced in food grade chrome plated brass material. These couplings are more durable and withstand higher pressures. They are available with internal shut-off valves or straight through designs. They are intuitive to use and make an audible "click" when coupled. The 40CB Series couplings interconnect with all other 40AC and 40PP Series couplings as well as other similar industry thumb-latch type couplings.





Features & Benefits

- Legacy metal thumb-latch couplings available with hose barb,
 PTF and threaded terminations
- Intuitive, easy-to-use design
- Audible click when coupled
- Available with internal shut-off valves or straight-through designs
- Interconnect with each other and with similar industry thumb-latch couplings

Specifications

Materials:

Bodies & Terminations: Food Grade Chrome/Brass Internal Valves: Acetal (POM) Internal Valve Springs: 316 Stainless Steel O-rings: Buna-N (others available)

O-rings: Buna-N (others available Thumb-latch: Stainless Steel

External Springs & Pins: Stainless Steel

Performance Ratings:

Operating Pressure: Vacuum to 250psi; (17.3bar) Temperature: -40°F to 180°F; (-40°C to 82°C)

Flow Capacity: 1/4" (6.4 mm)

Fits Tubing IDs: 1/4" (6.4 mm) - 3/8" (9.5 mm)





40CBSeries

1/4" Flow Size - Legacy Metal Latch

Part Style

Part Image

Open Flow Straight

1/4" (6.4 mm) tube ID & threaded 5/16" (7.9 mm) tube ID 3/8" (9.5 mm) tube ID & threaded Female and Male







Open Flow Panel Mount

1/4" (6.4 mm) tube ID 5/16" (7.9 mm) tube ID 3/8" (9.5 mm) tube ID Female and Male



Open Flow Elbow

1/4" (6.4 mm) tube ID 3/8" (9.5 mm) tube ID Male ONLY



Valved Straight

1/4" (6.4 mm) tube ID & threaded 5/16" (7.9 mm) tube ID 3/8" (9.5 mm) tube ID & threaded Female and Male





Valved Panel Mount

1/4" (6.4 mm) tube ID 5/16" (7.9 mm) tube ID 3/8" (9.5 mm) tube ID Female and Male



Valved Elbow

1/4" (6.4 mm) tube ID 3/8" (9.5 mm) tube ID Male ONLY





MAR-40CB-DS-01









Gamma Sterilizable Couplings with Larger Flow

Nordson MEDICAL's LinkTech line of 40PP quick connect couplings are produced from medical grade, gamma sterilizable polypropylene. These legacy metal latch couplings offer greater chemical resistance. They are available with internal shut-off valves or straight through designs. They are intuitive to use and make an audible "click" when coupled. These couplings are available in Legacy Almond and Modern Cool Grey colors. The 40PP Series couplings interconnect with all other 40AC and 40CB Series couplings as well as other similar industry thumb-latch type couplings.



Features & Benefits

- Legacy metal thumb-latch couplings available in hose barb, PTF and threaded terminations
- Offer greater chemical resistance
- Intuitive, easy-to-use design
- Audible click when coupled
- Available with internal shut-off valves or straight-through designs
- Available in 2 standard colors: almond and grey
- Interconnect with each other and with similar industry thumb-latch couplings

Specifications

Materials:

Bodies & Terminations: Medical Grade Polypropylene Internal Valves: Medical Grade Polypropylene Internal Valve Springs: 316 Stainless Steel O-rings: Peroxide-cured EPDM (others available) Thumb-latch: Stainless Steel

External Springs & Pins: Stainless Steel

Performance Ratings:

Operating Pressure: Vacuum to 120psi; (8.3bar) Temperature: 32°F to 160°F; (0°C to 71°C)

Flow Capacity: 1/4" (3.2 mm)

Fits Tubing IDs: 1/4" (6.4 mm) - 3/8" (9.5 mm) Sterilization: Gamma; 50kGy irradiation max





40PPSeries

1/4" Flow Size - Legacy Metal Latch

Part Style

Part Image

Open Flow Straight

1/4" (6.4 mm) tube ID & threaded 3/8" (9.5 mm) tube ID & threaded Female and Male



Open Flow Panel Mount

1/4" (6.4 mm) tube ID 3/8" (9.5 mm) tube ID Female and Male



Open Flow Elbow

3/8" (9.5 mm) tube ID Male ONLY



Valved Straight

1/4" (6.4 mm) tube ID & threaded 3/8" (9.5 mm) tube ID & threaded Female and Male





Valved Panel Mount

1/4" (6.4 mm) tube ID 3/8" (9.5 mm) tube ID Female and Male



Valved Elbow

3/8" (9.5 mm) tube ID Male ONLY



MAR-40PP-DS-01



