

T556

SAW SAFETY GUARD (FOR CIRCULAR SAW)



Materials:

(1-2) Polycarbonate.

Surface finish:

Satin.

Colour:

Orange (RAL 2004 code 02).

Inserts:

- (3) Aluminium rivet AL4.010 4.0x10.
- (4) Brass threaded through-hole insert.
- (5) Galvanised steel washer.
- (6) Turned galvanised steel pin with stop d.6x30.
- (7) Brass self-tapping screw M3x10 DIN 97.

Clamping lever:

Indexed clamping lever art. A523065.TM08X3001.

Special requests:

- Upon request and for special quantities the guard can be supplied in Yellow (RAL 1007) or in transparent version.
- Suction tube adapter D. 40 to be ordered separately - art. T556040.T01.

Product compliant with standard UNI EN 19085-5:2017.



Stock availability as % (🛒)
 90% (●) - 40% (●) - 5% (●)

🛒	Art.	L	A	B	H	D	d	d1	I	I1	I2	I3	I4	I5	I6	h1	h2	h3	h4
●	T556250.C03	337	30	60	147	60	53	6.5	80	243	77	16.5	10	23.5	42	75	57.5	28	23
●	T556300.C03	490	30	60	172	60	53	6	145	297	176	17	21.5	47.5	70	105	79.5	52	14.5

